



# KIT SE 1595

## Standard



FULL PIPE



MEDIA MEASURED  
LIQUIDS



PIPE DIAMETER  
FROM DN 80  
TO DN 4500

### SALES DESCRIPTION

- External probes for liquid flow measurement on a full pipe
- Standard applications – clear liquids and piping in good conditions
- Mounting on a pipe from DN80 to DN4500
- Maximum operating temperature of 80°C
- Push-Pull connectors

### INSTALLATION

Non intrusive

### APPLICATION

Full pipe

### CONDITIONS OF USE

Clear liquids, piping in good conditions

### DIAMETER OF THE PIPE

Recommended probe range: 100 – 3000 mm  
Extended probe range: 80 – 4500 mm (requires an 8XX converter)

### THICKNESS OF THE PIPE

> 1 mm

### CONNECTIC

Push – Pull connectors

### MOUNTING TYPE

/, V, N, W

### TEMPERATURE

From -20°C to +80°C

### SUPPORT

Included

### COMPATIBLE CONVERTERS

ALL

### ATEX CERTIFICATION

Possible (specific version)

### INGRESS PROTECTION

EN/IEC 60529 IP68

### MATERIAL OF THE PROBES

Plexiglass

### OVERALL SIZE

500 x 50 x 100 mm

### OVERALL WEIGHT (support & probes)

1280 g

### SENSOR FREQUENCY

500 kHz